



# LOADBREAK BUSHING INSERT WITH INDICATOR RING

## 15 AND 25 kV CLASS

### KEY FEATURES

- High quality peroxide-cured EPDM insulation
- Includes grounding tabs to attach a drain wire to maintain dead-front safety
- Provides insulated, fully shielded, submersible connection
- Conforms to ANSI/IEEE Standard 386
- Yellow indicator ring confirms proper installation

TE Connectivity's (TE) Raychem 200A loadbreak bushing insert is available in 15 kV and 25 kV classes. The bushing insert connects to a universal bushing well and is used in field installation and replacement of loadbreak elbows.

TE's Raychem bushing insert and elbow connectors provide fully shielded, submersible connection with conformance to IEEE Standard 386. These bushing inserts are therefore interchangeable with other manufacturers' products that also comply with this standard.

The yellow indicator ring provides installers a visual confirmation that the loadbreak elbow is properly seated on the bushing insert.

**Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.**

## Loadbreak Bushing Insert With Indicator Ring



### VOLTAGE RATINGS

Description	15 kV	25 kV
Minimum Partial Discharge	11	19
Max. Rating Phase-to-Ground	8.3	15.2
Max. Rating Phase-to-Phase	14.4	26.3
AC 60 Hz 1 Minute Withstand (rms)	34	40
DC 15 Minute Withstand	53	78
BIL and Full Wave (Crest)	95	125

### CURRENT RATINGS

Description	A rms
Continuous Current	200
Switching Current	200
Fault-closure Current for 0.17s after 10 Switching Operations	10,000 symmetrical
Short-time Current for 0.17s	10,000 symmetrical
Short-time Current for 3.00s	3,500 symmetrical

### PRODUCT SELECTION INFORMATION

Catalog Number	Product Description	Voltage Class	Current Rating
ELB-15-200-BI-IND	15 kV Bushing Insert	15 kV	200 A
ELB-25-200-BI-IND	25 kV Bushing Insert	25 kV	200 A

### RELATED TEST REPORTS

EDR 5630 (15 kV)

EDR 5631 (25 kV)

[te.com/energy](http://te.com/energy)

© 2015 - 2017 TE Connectivity. All Rights Reserved. EPP-2970-DDS-8\_2017-EN-AMS-Loadbreak-Insert-Indicator-RAY E834

Raychem, TE, TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this data sheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this data sheet are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

### FOR MORE INFORMATION: TE Technical Support Centers

USA:	+ 1 800 327 6996
Canada:	+ 1 (905) 475-6222
Mexico:	+ 52 (0) 55-1106-0800
Latin/S. America:	+ 54 (0) 11-4733-2200
France:	+ 33 380 583 200
UK:	+ 44 0870 870 7500
Germany:	+ 49 89 6089 903
Spain:	+ 34 916 630 400
Italy:	+ 39 333 250 0915
Benelux:	+ 32 16 508 695
Russia:	+ 7 495-790 790 2-200
China:	+ 86 (0) 400-820-6015